# Computer Networking from LANs to WANs: Hardware, Software, and Security Kenneta C. Mansfield Jr., James L. Antonakos

## Ch<sub>2</sub>

# True/False Indicate whether the statement is true or false. 1. The network cloud may comprise only the network found in a small laboratory, or it may represent an entire wide area network (WAN) such as the Internet. 2. With certain types of network communications, it is possible that duplicate packets of data are generated if an acknowledgement is not received by the source computer. 3. In a fully connected network, the number of connections at each node equals the total number of nodes plus one. 4. Even if the encrypted traffic is intercepted, chances are very small that the contents can be decrypted if a suitably strong encryption method and key are used. 5. A network that can be partitioned is secure and reliable. **Multiple Choice** *Identify the choice that best completes the statement or answers the question.* 6. The connections for the \_\_\_\_ of a network may be provided through dedicated phone lines, twisted pair cable, fiber optic cable line-of-sight microwave RF, ATM, or other form of electronic connection. a. physical topology c. physical infrastructure b. virtual topology d. virtual interconnection 7. When a large amount of data must be sent between machines on a network, it is possible to set up a \_\_\_\_ between the machines. a. permanent circuit c. virtual interface b. virtual circuit d. physical interface 8. A \_\_\_\_ uses public network connections to establish private communication by encrypting the data transmitted between the two computers at each end of the connection. c. PVN a. NPV b. VN d. VPN 9. Seven fully connected nodes require links. a. 14 c. 28 b. 21 d. 35 10. A network uses a single shared common communication media that all nodes tap into. a. ring c. bus b. star d. string 11. In a bus network, if two or more nodes transmit data at the same time, a \_\_\_\_ occurs. a. collision c. collusion b. compression d. contention 12. Token-ring networks, although logically viewed as rings, are connected using central \_\_\_\_\_.

c. station access units

a. media access units

		b. multistation access units	d. access units				
	13.	A(n) is a 32-bit number used to locate and a. MAC address b. TCP address	identify nodes on the Internet. c. Ethernet address d. IP address				
	14.	<ul><li>A is a portion of a network.</li><li>a. subnet</li><li>b. subunit</li></ul>	c. slice d. subdivision				
	15.	Companies that connect to a NAP enter into traffic. a. posting b. partner	agreements with each other that allow them to exchange c. peering d. polling				
Comp		o <b>n</b> each statement.					
	16.	A(n) circuit is a prearranged path through the network that all packets will travel for a particular session between machines.					
	17.	In a star network, all nodes connect to a central communications					
	18.	is a logical, not physical, activity and is accomplished using a special subnet mask, such as 255.255.255.192.					
	19.	A(n) network is owned and managed by a private organization or company and may have a much larger bandwidth capability than a public network.					
	20.	In terms of security and reliability, we must concern ourselves with what is required to our network.					
Matc	hing						
		<ul><li>Match each item with the correct statement below</li><li>a. Tunnels</li><li>b. Topology</li><li>c. Logical topology</li></ul>	ow. d. NAPs e. Cloud				
	21.	Concerns the structure of the connections between	en the computers in a network				
	22.	A graphical symbol used to describe a network	without specifying the nature of the connections				
	23.	Has to do with the path a packet of data takes th	rough the network				
	24.	Logical connections between the nodes of the V	PN				
	25.	Provide access to national and global network to	raffic				

# **Short Answer**

- 26. Describe a mesh network.
- 27. Discuss the difference between a hub and a switch.
- 28. Describe a hybrid network.
- 29. Discuss subnetting.
- 30. Describe a private network.

# Ch2

# **Answer Section**

# TRUE/FALSE

1.	ANS:	T	PTS:	1	REF:	22
2.	ANS:	T	PTS:	1	REF:	23
3.	ANS:	F	PTS:	1	REF:	25
4.	ANS:	T	PTS:	1	REF:	31
5.	ANS:	F	PTS:	1	REF:	31

## **MULTIPLE CHOICE**

22	REF:	1	PTS:	A	ANS:	6.
23	REF:	1	PTS:	В	ANS:	7.
23-24	REF:	1	PTS:	D	ANS:	8.
25	REF:	1	PTS:	В	ANS:	9.
26	REF:	1	PTS:	C	ANS:	10.
26	REF:	1	PTS:	A	ANS:	11.
27	REF:	1	PTS:	В	ANS:	12.
29	REF:	1	PTS:	D	ANS:	13.
29	REF:	1	PTS:	A	ANS:	14.
30	REF:	1	PTS:	C	ANS:	15.

# **COMPLETION**

16.	ANS:	virtual
10.	AIND.	viituai

115. 1 KL1. 2.	PTS:	1	REF:	23
----------------	------	---	------	----

17. ANS: hub

PTS: 1 REF: 25

18. ANS: Subnetting

PTS: 1 REF: 29

19. ANS: private

PTS: 1 REF: 30

20. ANS: partition

PTS: 1 REF: 31

# MATCHING

21. ANS: B PTS: 1 REF: 22

 22. ANS: E
 PTS: 1
 REF: 22

 23. ANS: C
 PTS: 1
 REF: 22

 24. ANS: A
 PTS: 1
 REF: 24

 25. ANS: D
 PTS: 1
 REF: 29

### **SHORT ANSWER**

### 26. ANS:

In general, a mesh network is a collection of computers that are not connected in a bus, star, or ring topology. The term full mesh, or fully connected mesh, is only used when each node is connected to each other node. A partially connected network does not have as many links as a full mesh, making it less reliable.

PTS: 1 REF: 25

### 27. ANS:

One characteristic of a hub is that it broadcasts data received on one port to all other ports, essentially sending copies of data from one node to all other nodes on the LAN. In this way, each node on the network has an opportunity to see each packet of network data. A similar device called a switch learns where to send the data, eliminating a large majority of the broadcast traffic on the LAN. The switch also provides the Star topology.

PTS: 1 REF: 26

### 28. ANS:

A hybrid network combines the components of two or more network topologies. Two star networks are connected (with three additional nodes) via a bus. This used to be a common way to implement Ethernet, with coax running between classrooms or laboratories and hubs in each room to form small subnetworks. Putting together a hybrid network takes careful planning, for there are various rules that dictate how the individual components may be connected and used. For example, when connecting Ethernet segments, a maximum of four repeaters may be used with five segments. Furthermore, if a 4-Mbps token-ring network is interfaced with a 10-Mbps Ethernet network, there are performance issues that must also be taken into consideration (because any Ethernet traffic is slowed down to 4Mbps on the token-ring side). In addition, the overall organization of the hybrid network, from a logical viewpoint, must be planned out as well.

PTS: 1 REF: 27

### 29. ANS:

Subnetting is a logical, not physical, activity and is accomplished using a special subnet mask, such as 255.255.255.192, that is logically ANDed with an IP address to determine its network address. The subnet mask is used to separate the IP address into two components: the network portion of the address and the host portion of the address. Here the host represents a node on the network. Nodes on different logical subnets cannot talk to each other without the use of a router, so using subnets allows the network designer to manage network traffic in a straightforward manner.

PTS: 1 REF: 29

# 30. ANS:

A private network is owned and managed by a private organization or company and may have a much larger bandwidth capability than a public network, depending on how much money its parent company invests in network infrastructure (by installing its own media between sites or by leasing private, dedicated communication lines from the telephone company). Private networks have higher maintenance costs per user and have the capability of restricting access to sensitive data.

PTS: 1 REF: 30-31